

## Polycarbonate panels with aluminium profile



Transparent roller shutters offer effective protection against burglary and with maximum transparency.

These gates are suitable for both indoor and outside use and are used to protect shop windows, shop entrances, arcades, business premises, industrial areas and for securing property. The profile rolls almost silently and has only a small diameter when rolled up. Protecting the object afterwards is also easy with the readymade box. In addition to polycarbonate panels, profiles KTP5 and KTP6 also offer panels made of closed aluminium and as grille profiles. We design and construct the transparent gate system for you – ready-assembled and in the highest quality – so that it is a perfectly adapted for its intended use.

**NEW!**




## Technical information

The curtain consists of horizontal, impact-proof polycarbonate panels with a thickness of 3, 5 or 6 mm. These are joined using extruded aluminium profiles.

The robust double-walled end rail is sealed with rubber. The curtain runs in aluminium guide rails with plastic guides.

The aluminium profiles are anodised as standard with E6EV1 and also available powder-coated if required.

### Product benefits

- Effective protection against break-ins
- Understated appearance for maximum transparency (85%)
- Available in pre-fabricated box system 
- Compact spooling with limited diameter when rolled up
- Reliable and robust
- Can be custom-designed

All roller shutter systems from Keroll comply with the valid standards and are supplied with comprehensive documentation and an individual production drawing.

Type	Shaft Ø (mm)	Curtain height (mm)	Box (W x H mm)
KTP3	70	2000	200 x 200
		3000	225 x 225
		4000	250 x 250
KTP5	70	2400	250 x 250
		3400	300 x 300
		4200	350 x 350
	102	1950	250 x 250
		3100	300 x 300
		4400	350 x 350
	133	5500	400 x 400
		2400	300 x 300
		3300	350 x 350
KTP6	102	5200	400 x 400
		6500	450 x 450
		2400	300 x 300
	133	3300	350 x 350
		4700	400 x 400
		6500	450 x 450
	159	2100	300 x 300
		2900	350 x 350
		4400	400 x 400
		5500	450 x 450
		6800	500 x 500
		1600	300 x 300
159	2500	350 x 350	
	3900	400 x 400	
	5050	450 x 450	
		6300	500 x 500

Type	Thickness polycarbonate (mm)	Dimensions aluminium profiles (W x H mm)	Weight (kg/m <sup>2</sup> )	Min. shaft Ø (mm)	Transparency (%)	max. width (mm)	Guide rails (mm)
KTP3	3	10 x 18	5,8	70	90	3.000	50 x 23 and 66 x 23
KTP5	5	17 x 28	8,0	70	85	6.000	110 x 38 and 80 x 38
KTP6	6	25 x 40	10,8	102	85	7.500	74 x 46 and 90 x 50

Please visit our homepage [keroll.de](http://keroll.de) for further information.

### Keroll Kerger GmbH

Otto-Hahn-Str. 8-10  
 D-42369 Wuppertal  
 Ph.: +49 (0) 2 02 / 2 46 57-0  
 Fax: +49 (0) 2 02 / 2 46 57-50  
 info@keroll.de · www.keroll.de

### Your specialist dealer: